

Two Stroke



ULTRA
LUBRICANTS

WORLD CLASS LUBRICANTS
FOR TROPICAL CONDITIONS

GENERAL

Ultra Two Stroke Motor Oil is a premium low ash lubricant, blended from refined hydro-treated base oils and an advanced additive package. It was formulated to impart high degrees of lubricity, detergency and dispersancy required for two stroke gasoline engines.

PERFORMANCE SPECIFICATIONS

The **Ultra Two Stroke Motor Oil** meets or exceeds the test requirements of:

- API TC
- ISO-EGB (JASO FB)

KEY BENEFITS

The use of **Ultra Two Stroke Motor Oil** would:

- Minimize spark plug fouling.
- Minimize deposits on pistons, the combustion chamber and exhaust parts.
- Provide maximum protection against piston and cylinder wear and bearing corrosion.

MAIN APPLICATIONS

Motorcycles, scooters, mopeds, chainsaws, generators, and other two stroke portable equipment where Two Stroke oils of JASO FB or TC performance levels are recommended.

TYPICAL PROPERTIES

	TEST METHOD	
Kin. Viscosity @ 40°C, cSt	ASTM D445	70.00
Kin. Viscosity @ 100°C, cSt	ASTM D445	9.36
Specific Gravity @ 60/60°F	ASTM D1298	0.867
Viscosity Index	ASTM D2270	111
Pour Point, °C	ASTM D97	-9
Closed Flash Point, °C	ASTM D93	99

HEALTH AND SAFETY

Ultra Two Stroke Motor Oil is unlikely to pose any health or safety hazards when used in the recommended applications provided good standards of personal and industrial hygiene are observed. Please refer to the Material Safety Data Sheet (MSDS) for further information.

Revision Date: 16/08/18

