

# Gear Oil HD & LSD

# **GENERAL**

Ultra Gear Oils HD & LSD are manufactured using refined hydro-treated base oils which are designed to provide outstanding benefits to cover the type of service encountered in high speed and/or high torque systems such as in hypoid gear units of passenger cars and other automotive gear units. These multi -purpose type lubricants are designed to meet the requirements of the SAE J2360, API GL-5, API MT-1 and MACK GO-J specifications and friction modified to meet the requirements of many limited slip differentials.

These oils incorporate <u>"Clean Gear Technology"</u> additives which keeps gears cleaned for longer intervals leading to improved maintenance and reduced failures.

### PERFORMANCE SPECIFICATIONS:

- SAE J2360.
- API MT-1,
- API GL-5,
- Mack GO-J
- Arvin Meritor O76-D (SAE 80W-90),
- Arvin Meritor O76-A (SAE 85W-140),
- Ford WSP-M2C197-A (SAE 80W-90).

## **MAIN APPLICATIONS:**

- Enclosed steel gears operating under load/speed conditions of extreme pressure.
- Automotive medium and low speed spur or helical gear units.
- Developed for car and commercial vehicles fitted with limited slip differentials.
- Spiral bevel and hypoid axle units on highway and off-highway vehicles.

### **Broad Application Coverage:**

- Recommended for Meritor axles assembled in many truck models by International, Freightliner, Volvo, Iveco. Ford and MAN.
- Recommended for Dana axles assembled in many truck models by Kenworth, International, Ford and MAN.

# **TYPICAL PROPERTIES**

|                             | TEST METHOD |        |         |
|-----------------------------|-------------|--------|---------|
| SAE Viscosity Grade         |             | 80W 90 | 85W 140 |
| Kin. Viscosity @ 40°C, cSt  | ASTM D445   | 166.30 | 355.20  |
| Kin. Viscosity @ 100°C, cSt | ASTM D445   | 16.25  | 26.00   |
| Viscosity Index             | ASTM D2270  | 101    | 97      |
| Specific Gravity @ 60/60°F  | ASTM D1298  | 0.8932 | 0.9024  |
| Closed Flash Point, °C      | ASTM D93    | 182    | 190     |

# **HEALTH AND SAFETY**

**Ultra Gear Oils** are unlikely to pose any health or safety hazards when used in the recommended applications, provided good standards of personal and industrial hygiene are observed. Please refer to the Material Data Sheet (MSDS) for further information.

Revision Date: 16/08/18

