



ULTRA
LUBRICANTS

WORLD CLASS LUBRICANTS
FOR TROPICAL CONDITIONS

CVT FLUID

GENERAL

Ultra Full Synthetic CVT Fluid is a multi-vehicle continuous variable transmission (CVT) fluid suitable for use in most belt or chain CVT applications. Formulated with synthetic base stocks to insure long life and compounded with state of the art additive technology to insure exceptional metal-to-metal frictional properties and provide outstanding anti-shudder durability.

Ultra Full Synthetic CVT Fluid is recommended for use in virtually all chain and belt driven CVT transmissions. This product provides engineered anti-shudder performance for smooth transfer of power in highly sophisticated variable drive transmissions found in many newest cars and SUV's. Check owner's manual for specific recommendations.

NOTE: Not for use in hybrid CVT units such as those in the Toyota Prius or Ford Escape.

KEY BENEFITS:

- Full synthetic long life formula.
- Outstanding metal-to-metal friction performance.
- Excellent wear resistance.
- Excellent low temperature fluidity.
- Outstanding anti-shudder durability.

Ultra Full Synthetic CVT Fluid is suitable for use in:

Audi CVT G052 180 A2 (TL52180)	Mini Cooper EZL799
BMW EZL 799	Mitsubishi CVTF-J1
Daihatsu AMMIX CVT, TC	Mitsubishi CVTF-J4
Dodge/Jeep/Chrysler NS-2	Mitsubishi SP-III (CVT)
Dodge/Chrysler/Jeep CVT+4	Nissan CVT NS-1, -2, -3
Ford CFT or CVT 23	Subaru DEX CVT (VTF)
Ford/Mercury <3.5L engine XT-7-QCFT (VFT/CVT)	Subaru iCVT
GM/Saturn DEX-CVT	Subaru CVT SOA868V9245QT
Honda CVT Fluid	Subaru iCVT FG
Honda HMMF (without starting clutch)	Subaru ECVT
Honda HCF2	Subaru Chain CVT Lineartronics
Honda Z-1 (CVT model)	Suzuki CVTF TC
Hyundai/Kia CVT-J1, SP III (CVT)	Suzuki CVTF 3320
JASO M315-2013 1A	Suzuki NS-2
JASO M315-2013 1A-LV	Suzuki CVT Green 1 & 2
JASO M315-2013 2A	Toyota CVTF TC
Mazda JWS 3320, TC	Toyota CVTF FE
MB 236.20	VW CVT (TL 52180, G 052 180 A2)

TYPICAL PROPERTIES

	TEST METHOD	
SAE Viscosity Grade	SAE J-300	20
Kin. Viscosity @ 40°C cSt	ASTM D445	35.9
Kin. Viscosity @ 100°C cSt	ASTM D445	7.33
Viscosity Index	ASTM D2270	174
Specific Gravity 60/60°F	ASTM D1298	0.849
Brookfield Viscosity @ -40°C	ASTM D5393	13,780
Colour		Red
Pour Point °C	ASTM D97	-42
Flash Point, (PMCC) °C	ASTM D93	204

HEALTH AND SAFETY

Ultra Full Synthetic CVT Fluid is unlikely to pose any health or safety hazards when used in the recommended applications, provided good standards of personal and industrial hygiene are observed. Please refer to the Material Safety Data Sheet (MSDS) for further information.

Revision Date 19/01/18